

# Apollo



**120**  
**Shield**



**180**  
**Python**



**320**  
**Sunlight**



**510**  
**Enlighten**



**515**  
**Bronze**



**530**  
**Wreath**



**545**  
**New Eng Blackbutt**



**555**  
**Grafton Spot.Gum**



**570**  
**Western Blackbutt**



**625**  
**Tallowood**



**710**  
**Oracle**



**730**  
**Dolphin**

Specifications and colourations are subject to manufacturing tolerances. As part of the Godfrey Hirst continuous improvement program, Godfrey Hirst reserves the right to change the specifications of or delete colours of this product without notice. While all care is taken, product images may vary in colour due to possible printing process variations. Images do not seek to duplicate the exact visual appearance, but serve merely as a guide or point of reference.

# Apollo

Apollo captures the natural beauty of timber with the best attributes of a laminate and vinyl flooring. The innovative hybrid flooring delivers astonishing durability and impact resistance.

## Technical Data

<b>Type:</b>	Hybrid Flooring	<b>Finish:</b>	Matte
<b>Dimensions:</b>	1220mm x 180mm	<b>Surface:</b>	Embossed
<b>Total Product Thickness:</b>	5.8mm	<b>Top Layer:</b>	Decorative Film & Wear Layer
<b>Wear Layer:</b>	0.3mm	<b>Substrate Layer:</b>	Trigon® Core Technology (Limestone Composite)
<b>Units Per Box:</b>	10 boards	<b>Backing Layer:</b>	1.5mm Acoustic Backing
<b>m<sup>2</sup> per box:</b>	2.196	<b>Profile:</b>	Micro Bevel
<b>m<sup>2</sup> per pallet:</b>	131.76	<b>Coating System:</b>	UV Coating
<b>Colours:</b>	12	<b>Installation Method:</b>	Unipush®
<b>Country of Origin:</b>	China		

## Performance

<b>Dimensional Stability:</b>	(ISO 23999) Length: 0.05%, Width: -0.05%, Curling: 0.00%	<b>Flammability:</b>	(EN ISO 9239) CRF 10.6kW/m <sup>2</sup>
<b>Abrasion Rating:</b>	(EN 660-2) Group T	<b>Smoke Value:</b>	(EN ISO 9239) 92% minutes
<b>Impact Sound Reduction:</b>	Please refer to Godfrey Hirst Acoustic Performance specification sheet	<b>Slip Resistance:</b>	(AS 4586) P3
<b>Light Fastness:</b>	(EN ISO 105-B02) Grade 6	<b>Warranty:</b>	15 Year Hybrid Limited Residential Warranty*
<b>Light Reflectance Values:</b>	Available on Request		

## Sustainability

<b>Product Transparency:</b>	Global Green Tag, GreenRate Level A certified
<b>Accreditation:</b>	Manufactured under a quality and environmental system certified and complying with ISO 9001 and ISO 14001 by an accredited certification body.
<b>Indoor Air Quality:</b>	Green Building Council Compliant for VOC emission rate limits

Trigon Core Technology	Global Green Tag	ISO 9001 Quality Management System	ISO 14001 Environment Management System	Micro Bevel Edge	Embossed	Matte Finish	Waterproof Surface <sup>^</sup>	15 Year Hybrid Limited Residential Warranty*
0.3mm Wear layer	Affordable							

All Godfrey Hirst hybrid floors products must be installed in accordance with relevant Australian Standards and in conjunction with the Godfrey Hirst Hybrid Flooring Installation Instructions.  
 \*This product comes with a residential warranty for new product installed indoors in a residential home, if properly installed and maintained. This warranty is in addition to consumers' rights under the statutory consumer guarantee provisions in the Australian Consumer Law, which may exceed the rights under this warranty. The amount recoverable under the warranty decreases after five years. For full information in respect to the scope and limitations of this warranty, please refer to the full terms and conditions available from your retailer, by calling 1300 444 776, or by download from [www.godfreyhirst.com](http://www.godfreyhirst.com).  
 † Terms and conditions apply to all commercial warranties - contact your GH Commercial Account Manager.  
 ^Subject to proper installation, maintenance and local building code/regulatory approval.